

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Cancelled)

2. (Currently Amended) In a steering apparatus for a vehicle, comprising:

an upper bracket fixed to a rear side portion of a vehicle body and including a pair of opposed flat plate portions formed with first holes opposing each other and separated from each other;

a lower bracket fixed to a front side portion of the vehicle body and including a pair of opposed flat plate portions formed with second holes opposing each other and separated from each other;

a steering column rotatably supporting a steering shaft;

a first support member held between said opposed flat plate portions of said upper bracket, formed with a first support holes opposing to the first holes and supporting said steering column;

a second support member held between said opposed flat plate portions of said lower bracket, formed with a second support holes opposing the second holes and supporting said steering column;

a third support member for supporting a harness member between said first support member and said second support member;

a first support mechanism for supporting said steering column on said upper bracket via the first holes of said upper bracket and via the first support holes of said ~~lower bracket~~ first support member; and

a second support mechanism for supporting said steering column on said lower bracket via the second holes of said lower bracket and via the second support holes of said second support member,

an improvement characterized in that said steering column is integrally formed with at least two said

support members among said first support member, said second support member and said third support member,

said first support member is integrally formed with a first swelling portion having a pair of side portions that respectively press-abut on said pair of opposed flat plate portions of said upper bracket,

said second support member is integrally formed with a swelling portion having a pair of side portions supported respectively via a hinge device on said pair of opposed flat plate portions of said lower bracket, and

said third support member is integrally formed with a third swelling portion having a third support hole for fixing a support member that supports said harness member.

3. (Original) A steering apparatus for a vehicle according to claim 2, wherein said third support member is formed on said first swelling portion, formed extending toward a front side of a vehicle body, of said first support member.

4. (Currently Amended) ~~A steering apparatus for a vehicle according to claim 1,~~ In a steering apparatus for a vehicle, comprising:

an upper bracket fixed to a rear side portion of a vehicle body and including a pair of opposed flat plate portions formed with first holes opposed each other and separated from each other;

a lower bracket fixed to a front side portion of the vehicle body and including a pair of opposed flat plate portions formed with second holes opposed each other and separated from each other;

a steering column rotatably supporting a steering shaft;

a first support member held between said opposed flat plate portions of said upper bracket, formed with first support holes opposing the first holes and supporting said steering column;

a second support member held between said opposed flat plate portions of said lower bracket, formed with second support holes opposing the second holes and supporting said steering column;

a first support mechanism for supporting said steering column on said upper bracket via the first holes of said upper bracket and via the first support holes of said first support member; and

a second support mechanism for supporting said steering column on said lower bracket via the second

holes of said lower bracket and via the second support
holes of said second support member,

an improvement characterized in that said steering
column is integrally formed with said first support
member and said second support member,

said first support member is integrally formed with
a first swelling portion having a pair of side portions
that respectively press-abut on said pair of opposed flat
plate portions of said upper bracket, and

said second support member is integrally formed with
a second swelling portion having a pair of side portions
that respectively press-abut on said pair of opposed flat
plate portions of said lower bracket,

wherein a respective protruded portion protruding
inward along the whole of ~~the~~ each first support hole is
formed along a peripheral edge of said first support
hole.

5. (Currently Amended) A steering apparatus for a
vehicle according to claim 3, wherein ~~the~~ each first hole
of said upper bracket is an elongate hole for adjusting a
tilt position,

said second support mechanism is a hinge mechanism
for rotatably supporting said steering column, and

said first support mechanism holds and fixes said first support member between said pair of opposed flat plate portions of said upper bracket, or releases said first support member to enable said steering column to move.

6. (Currently Amended) A steering apparatus for a vehicle according to claim 5, wherein ~~both of the~~ first support holes of said first support member and the second support holes of said second support member are elongate holes for adjusting a telescopic position of said steering column.

7. (Cancelled)

8. (Currently Amended) ~~A steering apparatus for a vehicle according to claim 7,~~ In a steering apparatus for a vehicle, comprising:

a steering column for rotatably supporting a steering shaft; and

a vehicle-body-rear-side bracket and a vehicle-body-front-side bracket, fixed to a vehicle-body-side strengthening member, for supporting said steering column,

an improvement characterized in that said steering column is integrally formed with a plurality of swelling portions and is supported on said vehicle-body-rear-side bracket and/or said vehicle-body-front-side bracket via said swelling portions,

wherein a harness member supporting member is attached via one of said swelling portions.

9. (Currently Amended) A steering apparatus for a vehicle according to claim 2, wherein a respective protruded portion protruding inward along the whole of ~~the~~each first support hole is formed along a peripheral edge of said first support hole.